



Utility/Ag Tractors  
M95S/105S



SPECIFICATIONS

MODEL		M95SDSC (4WD)	M105SDSC (4WD)	M105SHC (2WD)	M105SHDC (4WD)	
Engine	Model	V3800-DI-T	V3800-DI-TI			
	Type (Make: KUBOTA)	direct injection, liquid cooled 4-cylinder diesel				
	Aspiration	Turbocharged	Turbocharged w/intercooler			
	Rated speed rpm	2600				
	PTO horsepower HP (kW)	84 (62.7)	93 (69.4)			
	Net engine horsepower HP (kW)	95 (70.9)	105 (78.3)			
	Total Displacement cu.in. (cc)	230 (3769)				
	Fuel tank capacity gal. (l)	46 (175)				
	Air cleaner	Dry, dual element				
	Alternator Amp	60 (80 M95SDSCC/M105SDSCC models*)				
Transmission	No. of speeds	32 forward / 32 reverse forward / 48 reverse w/opt. creep)	(48	16 forward / 16 reverse forward / 24 reverse w/opt. creep)	(24	
	Main gear shift (4 speeds)	Fully synchronized				
	Hydraulic-shuttle	Steering column-mounted lever				
	Main clutch type / Brake type	Hydraulic wet discs / Hydraulic wet discs				
	Mechanical differential lock	Standard(Front & Rear)		Standard (Rear)	Standard (Front & Rear)	
PTO System	PTO type	Hydraulic independent PTO with PTO brake, wet discs				
	Speed	540 rpm (540 / 100 rpm optional)				
Hydraulics	Pump capacity (3-point hitch) gpm	17.2				
	3-point hitch	Telescopic lower link ends, Telescopic stabilizers				
	Category	Category II				
	Control system	Position, draft (top link sensing) & mix control				
	Lift capacity 24" behind lift point lbs.(kgf)	4630 (2100), 7490 (3400) w/2 assist cylinders (optional)				
Other Features	No. of standard remote valves	1 standard (2nd, 3rd & flow control valve optional)			(2	
	4WD drive system	Bevel gear type		N/A	Bevel gear type	
	Steering	Hydrostatic power steering				
Other Features	Hood Type	Single piece full open hood, twin gas shock assist				
	Deck type / Pedal type	ISO-mounted full flat deck with rubber mat/hanging pedals				
Dimensions & Weight	Tire size (**)	Front/rear	12.4-24/18.4-30 cast	13.6-24/18.4-34 cast	10.0-16/18.4-34	13.6-24/18.4-34 cast
	Overall length in. (mm)	162 (4120)				
	Overall height (w /Cab) in. (mm)	106 (2680)				
	Overall width in. (mm)	79 (2010)				
	Wheelbase in. (mm)	95.9 (2435)				
	Ground clearance (Drawbar bracket) in. (mm)	17.1 (435)				
	Tread width Front in. (mm)	60.2-65.4 (1530-1660)		60.6-80.3 (1540-2040)	60.2-65.4 (1530-1660)	
		in. (mm)		60.2-80.1 (1530-2035)****	59.0-79.0 (1500-2005)	60.2-80.1 (1530-2035)****
	Turning radius w/brake ft. (m)	15.4 (4.7)**		12.5 (3.8)	15.4 (4.7)**	
	Tractor Weight *** lbs. (kg)	7628 (3460)	7628 (3460)	7055 (3200)	7628 (3460)	
Tractor Weight **** lbs. (kg)	8642 (3920)	8642 (3920)	8069 (3660)	8642 (3920)		

\* For cold weather regions.

\*\* Optional tire size and Radial tires available.

\*\*\* 4WD engaged.

\*\*\*\* w/cast iron disks for rear wheels

All standard equipment in base model machines except where noted.

The company reserves the right to change the above specifications without notice.

These Specifications are for descriptive purpose only. Please contact your local Kubota dealer for warranty information.

For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.