



SPECIFICATIONS

MODEL		MX5000SU 2WD		
Engine	Model	V2403		
	Type	E-TVCS, Indirect injection, liquid cooled diesel		
	PTO horsepower	HP (kW)	44 (32.8)	
	Engine gross horsepower	HP (kW)	52.2 (38.9)	
	Rated RPM	2700 rpm		
	Bore and stroke	in. (mm)	3.4x4.0 (87x102.4)	
	Displacement	cu. In. (cc)	148.5 (2434)	
	Air cleaner	Dry, dual element		
	Battery	12V, 55Ah, 582-cold cranking amps at-18°C		
	Cooling system	Heavy duty pressurized radiator		
Transmission/ Drive train	Clutch	Dry-type single stage		
	Transmission	Mechanical shuttle constant mesh 8F/4R		
	Traveling speeds (w/std. Ag tires)		Forward	Reverse
			Low / High	Low
		First	1.27(2.04) / 4.85(7.80)	1.71 (2.75)
		Second	1.79 (2.88) / 6.85 (11.80)	2.42 (3.89)
	Third	2.91 (4.68) / 11.13 (17.91)	3.93 (6.32)	
	Fourth	4.29(6.91) / 16.44(26.45)	5.80 (9.33)	
Differential lock	Standard			
Final drive	Spur Gear			
PTO System	Brake	Mechanical wet disc		
	Type	Hydraulic, Live-Independent		
Hydraulics	Rear	540		
	Type	Open Center		
	Pump	Tandem, Gear		
	Total pump output	gpm (l/min)	14.0 (53.0)	
	Hydraulic outlet	Optional (1 - 2 - 3)		
	3-point hitch	Category I and II		
	Hydraulic control system	Position control (Draft control optional)		
	Lift capacity at lift point	lbs. (kg)	2866 (1300)	
	24" behind LP	lbs. (kg)	2315 (1050)	
Capacities	Steering	Hydrostatic power steering		
	Fuel tank	gal. (l)	13.2 (50)	
	Cooling system	qts. (l)	7.9 (7.5)	
	Engine oil	qts. (l)	8.0 (7.6)	
Transmission case	gal. (l)	11.6 (44)		



SPECIFICATIONS

MODEL		MX5000SU 2WD
Dimensions & Weight	Overall length (w/o 3P) in.(mm)	2WD: 132.5 (3365)
	Overall width (min tread) in. (mm)	62.4 (1585)
	Overall height (w/ROPS) in. (mm)	84.8 (2155)
	Wheelbase in. in. (mm)	2WD: 71.6 (1821)
	Ground clearance (Front Axle) in. (mm)	2WD: 15.9 (405)
	Tread width	Front: 48.8 - 59.6 (1215-1515)
	Turning radius w/brake ft. (m)	2WD: 8.5 (2.6)
	Weight with ROPS lbs. (kg)	F (2WD)= 3285 (1490)
Tire Size	Ag Standard Front/Rear	2WD: 7.5L-15 F2/14.9-26 R1
	Turf Option Front/Rear	2WD: 29x12.5-15/44 18-20

All standard equipment in base model machines except where noted.

The company reserves the right to change the above specifications without notice.

These Specifications are for descriptive purpose only. Please contact your local Kubota dealer for warranty information.

For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.