



KX Ultra-Compact Excavators
K008-3



SPECIFICATIONS

MODEL			K008-3
Engine	Model		Kubota D722
	Horsepower	HP / rpm	10.2 / 2050
	Displacement	cu. In.	44.0
Dimension	Overall length	in.	108.0
	Overall height	in.	88.0
	Overall width	in.	28 / 34
	Rear tail turning radius	in.	30.0
Working range	Max. digging height	in.	113
	Max. dumping height	in.	80
	Max. digging radius @ ground	in.	119
	Max. digging depth	in.	67.5
	Max. vertical digging depth	in.	54
Hydraulic System	Pump capacity	gal/min	5.6
	Auxiliary hydraulic line flow rate	gal/min	5.5
	Bucket breakout force	lbs	2200
Drive system	Max. traveling speed	mph	1.2 / 2.5
	Max. drawbar pull		1390
	Under carriage shoe width		7.1
	Ground contact pressure	psi	3.5
Swing system	Unit swing speed	rpm	8.3
	Boom swing angle (L / R)	degree	55 / 60
Blade	Blade width x height		28 / 34 x 7.9
	Max. lift above ground		7.9
	Max. drop below ground		7.1
Capacities	Fuel reservoir	gal	3.2
	Hydraulic reservoir	gal	3.3
Operating weight		lbs (tons)	2200 (1.0)

All standard equipment in base model machines except where noted.

The company reserves the right to change the above specifications without notice.

These Specifications are for descriptive purpose only. Please contact your local Kubota dealer for warranty information.

For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.