



KX Compact Excavators

KX41-3



SPECIFICATIONS

MODEL			KX41-3
Engine	Model		Kubota D902
	Horsepower	HP / rpm	17 / 2300
	Displacement	cu. In.	54.8
Dimension	Overall length	in.	144.0
	Overall height	in.	90.0
	Overall width	in.	39 / 51.2
	Min. ground clearance	in.	6.3
Working range	Max. digging height	in.	140
	Max. dumping height	in.	97.2
	Max. digging radius @ ground	in.	152.4
	Max. digging depth	in.	93.7
	Max. vertical digging depth	in.	74.6
Hydraulic System	Pump capacity	GPM	13.7
	Auxiliary hydraulic flow rate	GPM	7.4
	Max. bucket breakout force	lbs.	3505
Drive system	Traveling speed	mph	1.5 / 2.6
	Max. drawbar pull	lbs.	2899
	Under carriage shoe width	in.	9.1
	Ground contact pressure	psi	3.8
Swing system	Unit swing speed	rpm	9.1
	Boom swing angle (L / R)	degree	73 / 50
Blade	Blade width x height	in.	39 / 51.2 x 9.1
	Max. lift above ground	in.	7.9
	Max. drop below ground	in.	8.5
Fuel reservoir	Fuel reservoir	gal.	5.6
Hydraulic reservoir	Hydraulic reservoir	gal.	3.7
Weight	Operating weight	lbs. (tons)	3693 (1.7)

All standard equipment in base model machines except where noted.

The company reserves the right to change the above specifications without notice.

These Specifications are for descriptive purpose only. Please contact your local Kubota dealer for warranty information.

For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.