



KX Compact Excavators
KX91-3



SPECIFICATIONS

MODEL			KX91-3
Engine	Model		Kubota D1503
	Horsepower	HP/rpm	28 / 2300
	Displacement	cu. In.	91.5
Dimension	Overall length	in.	187.4
	Overall height	in.	96.1
	Overall width	in.	61.0
	Min. ground clearance	in.	11.6
Working Range Long Stick	Max. digging height	in.	195
	Max. dumping height	in.	139
	Max. digging radius @ ground	in.	202
	Max. digging depth	in.	125
	Max. vertical digging depth	in.	94
Hydraulic System	Pump capacity	GPM	27.3
	Auxiliary hydraulic flow rate	GPM	10.9
	Max. bucket breakout force	lbs	8059
Drive System Low Traction Force	Traveling speed	mph	1.9 / 2.9
	Max. drawbar pull	lbs	8363
	Under carriage shoe width	in.	11.8
	Ground contact pressure	psi	4.5
Swing system	Unit swing speed	rpm	9.4
	Boom swing angle (L / R)	degree	80 / 50
	Blade width x height	in.	61 x 13.2
	Max. lift above ground	in.	14.6
	Max. drop below ground	in.	14.6
Fuel Reservoir		gal.	11.9
Hydraulic Reservoir		gal.	9.5
Operating Weight		lbs (tons)	7110 (3.2)

All standard equipment in base model machines except where noted.

The company reserves the right to change the above specifications without notice.

These Specifications are for descriptive purpose only. Please contact your local Kubota dealer for warranty information.

For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.