



SPECIFICATIONS

MODEL		L2800			L3400			L4400		
		Gear-Drive		HST	Gear-Drive		HST	Gear-Drive Transmission		
		2WD	4WD	4WD	2WD	4WD	4WD	2WD	4WD	
Engine	Type (Make: KUBOTA)	Vertical liquid-cooled 4-cycle diesel, Indirect injection (E-TVCS)								
	Engine gross power	HP (kW)	29.0 (21.6)@2800 rpm		34.7 (25.9)@2700 rpm		45.3 (33.8)@2600 rpm			
	PTO Power	HP (kW)	24.0 (17.9)	22.5 (16.8)	29.0 (21.6)	27.5 (20.5)	37.5 (28.0)			
	No. of cylinders		3				4			
	Bore and stroke	in. (mm)	3.1x3.6 (80x92.4)			3.4x3.6 (87x92.4)				
	Total displacement	cu.in. (cm ³)	85.0 (1393)			100.5 (1647)		134.1 (2197)		
	Battery		12V, RC:123min, CCA:490A					12V, RC:133min, CCA:582A		
	Fuel tank capacity	US gal. (l)	9.0 (34)					11.3 (43)		
PTO	Rear PTO (540 rpm)	Transmission driven with overrunning clutch	Live-continuous with ORC	Live-continuous running	Live-continuous with ORC	Hydraulic, Live-independent				
Hydraulic	Pump capacity (main)	gpm (l/min)	6.5 (24.7)		6.3 (23.9)		7.8 (29.4)			
	Pump capacity (PS)	gpm (l/min)	4.0 (15.0)		3.8 (14.5)		4.7 (17.9)			
	3-point hitch		Category I							
	Lift control type		Position Control							
	Lift capacity at lift point	lbs. (kg)	1998 (906)					2870 (1300)		
	Lift capacity: 24in. behind LP	lbs. (kg)	1435 (651)					2310 (1053)		
Traveling System	Transmission	Sliding gear and Constant Mesh, 8 forward and 4 reverse	Hydrostatic transmission 3 range speed	Sliding gear and Constant Mesh, 8 forward and 4 reverse	Hydrostatic transmission 3 range speed	Sliding gear and Constant Mesh, 8 forward and 4 reverse				
	Steering	Integral type power steering					Hydrostatic power steering			
	Brakes	Wet disc type								
	Clutch	Dry-type single stage			Dry-type dual stage		Dry-type single stage			
	Rear differential lock	Standard								
Ag Standard	Front/Rear	5-15/11.2-24	7-16/11.2-24		5-15/11.2-24	7-16/11.2-24		7.5L-15/14.9-24	8.3-16/14.9-24	
	Ag Option	Front/Rear	N/A					6.0-16/14.9-24	N/A	



Compact Tractors
L2800 / L3400 / L4400



SPECIFICATIONS

MODEL		L2800			L3400			L4400	
		Gear-Drive		HST	Gear-Drive		HST	Gear-Drive Transmission	
		2WD	4WD	4WD	2WD	4WD	4WD	2WD	4WD
Tire Size	Turf Option	Front/Rear		2WD: 23x8.50-12/13.6-16 4WD: 25x8.50-14/13.6-16			27x8.50-15/44x18-20	[27-10.5/44x18-20], [27x8.50-15/44x18-20]	
	Industrial Option	Front/Rear		N/A	27x8.50-15/15-19.5R4		N/A	27x8.50-15/15-19.5R4	
Traveling Speeds	With standard AG tires (at Rated Engine Speed)	mph (km/h)		Forward	Reverse	Forward	Reverse	Forward	Reverse
		1.1(1.8)-13.7(22.0) 0(0)-13.2(21.2)		1.1(1.7)-13.2(21.2) 1.5(2.4)-4.7(7.6)		1.2(2.0)-14.9(24.0)		1.5(2.4)-5.1(8.2)	
Dimensions	Overall length (w/o 3P)	in. (mm)		110.6 (2810)	106.5 (2705)		110.6 (2810)	106.5 (2705)	
	Overall width (min. tread)	in. (mm)		51.4 (1305)			62.4 (1585)		
	Overall height (w/ ROPS)	in. (mm)		85.0 (2160)			85.4 (2170)		
	Wheelbase	in. (mm)		63.3 (1610)			72.8 (1850)	72.6 (1845)	
	Min. ground clearance	in. (mm)		13.6 (345)	13.4 (340)		13.6 (345)	13.4 (340)	
	Tread(standard front tires)	in. (mm)		41.3 (1050)	43.1 (1095)		41.3 (1050)	43.1 (1095)	
	Tread(standard rear tires)	in. (mm)		40.2 (1020), 43.8 (1115), 47.1 (1195), 50.8 (1290)			46.5(1180), 47.2(1200), 51.2(1300), 57.1(1450),		
Minimum turning radius (with brake)	feet (m)		7.9 (2.4)	8.2 (2.5)		7.9 (2.4)	8.2 (2.5)		
Weight (with ROPS)	lbs. (kg)		2359(1070)	2536(1150)	2600(1180)	2403(1090)	2580(1170)	2600(1180)	3031(1375) 3153(1430)
Optional Equipment	Sunshade, Front Bumper Weights, Rear Wheel Weights, Block Heater, Drawbar Clevis, 3PT Stabilizer Kit , Aux. Control Valves, Grill Guard, Double Element Air Cleaner*, Rear Work Light, Draft Control Kit (L4400), 3PT Top-N-								

* Standard on L4400.

The company reserves the right to change the above specifications without notice.

These Specifications are for descriptive purpose only. Please contact your local Kubota dealer for warranty information.

For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.