



### SPECIFICATIONS

MODEL	L48		
Engine	Gross power (SAE)	HP (kW)	48 (35.8)
	Net power (SAE)	HP (kW)	46 (34.3)
	Total displacement	cu. In. (cm <sup>3</sup> )	148.5 (2434)
	No. of cylinders		4
	Rated speeds		2600 rpm
Transmission/ Drive Train	Type		HST (3 Range)
	No. of speeds		Infinite
	Clutch		Dry, Single
	Power Steering		Hydrostatic
	Max. traveling speed	mph (km/h)	16.1 (26)
	Shift lever position		Seat side, right
PTO System	Max PTO Power	HP (kW)	37.5 (27.8)
	Rear PTO		540 rpm, Live-continuous running
Hydraulic System	Type		Open center/constant flow
	Pump capacity	gpm. (l/min.)	25.9 (98.1)
	Maximum operating pressure		2800
	3-Point Hitch Type		Category I
	3-Point Hitch lift capacity at 24 in. (610 mm) behind lift point	lbs. (kg)	3310 (1500)
	Position control		Standard
Dimensions & Weight	Fuel Tank Capacity	gal. (l)	13.2 (50)
	Wheel Base	in. (mm)	74.0 (1880)
	Front Tread	in. (mm)	53.7 (1363)
	Rear Tread	in. (mm)	57.6 (1462)
	Weight with Loader, Backhoe and ROPS/FOPS	lbs. (kg)	7760 (3520)
	Min. Turning Radius with brake	ft. (m)	11.1 (3.4)
ROPS/FOPS			4 Post, with retractable seatbelt
Tire Size	Front		10-16.5R4
	Rear		17.5L-24R4
Other Performance Features	Hood		Slanted hard nose hood
	Frame		Loader-integrated reinforced frame
	Brakes		Wet Disc Brakes
	Seat		Reversible seat
	Steering Wheel		Tilt steering
	Muffler		Enclosed Muffler with Spark Arrestor
	Pedals		Hanging type pedals
Deck		Full-Floating ISO-Mounted Flat Deck	

All standard equipment in base model machines except where noted.

The company reserves the right to change the above specifications without notice.

These Specifications are for descriptive purpose only. Please contact your local Kubota dealer for warranty information.

For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.