



SPECIFICATIONS

MODEL		M9000 Mudder (ROPS)			M9000 Mudder (Cab)		
Engine	Engine Model	V3300-TIE					
	Type	E-TVCS, Indirect injection, liquid cooled diesel					
	PTO horsepower	HP (kW)	80 (59.7)				
	Net engine horsepower	HP (kW)	90 (67.2) @ 2600 rpm				
	Bore and stroke	in. (mm)	3.86x4.33 (98x110)				
	Displacement	cu. In. (cc)	202 (3318)				
	Air cleaner		Dry, dual element				
	Battery		12V, 1000 CCA				
Transmission/ Drive train	Cooling system	Heavy duty pressurized radiator					
	Clutch	Dry Single Plate					
	Transmission	4-speed, fully synchronized main (12F x 12R)					
	Traveling speeds (w/std. Ag tires)	Forward			Reverse		
		Creep	Low	High	Creep	Low	High
	First	0.14	1.20	5.00	0.14	1.20	4.90
	Second	0.22	1.90	7.60	0.22	1.80	7.60
	Third	0.34	2.90	11.80	0.34	2.80	11.70
Fourth	0.46	3.90	16.00	0.46	3.80	15.80	
PTO System	Differential Lock	Standard					
	Final drive	Inboard planetary					
	Brake	Mechanical multi-plate wet disc					
	Type	Hydraulic, Live-Independent					
Hydraulics	Rear	540 rpm (540 / 1000 rpm optional)					
	Type	Open Center					
	Pump	Gear Pumps					
	Total pump output	gpm (l/min)	23.1 (87.4)				
	Remote output	gpm (l/min)	17.0 (64.3)				
	Hydraulic outlet	1 Standard (3 optional, 2 optional with flow control)					
	3-point hitch	Category II					
	Hydraulic control system	Position with draft and mix control					
Capacities	Lift capacity 24" behind LP	lbs. (kg)	4630 (2100) / 6393 (2900) Optional				
	Steering	Hydrostatic power steering					
	Fuel tank	gal. (l)	23.8 (90)				
	Cooling system	qts. (l)	9.5 (9.0)				
Dimensions & Weight	Engine oil	qts. (l)	11.3 (10.7)				
	Transmission case	gal. (l)	13.7 (52)				
	Overall length (w/3P)	in. (mm)	159.8 (4060)				
	Overall width (min tread)	in. (mm)	79.1 (2010)				
	Overall height (ROPS/Cab)	in. (mm)	107.4 (2730) / 113.1 (2873)				
	Wheelbase in.	in. (mm)	88.6 (2250)				
	Ground clearance (Front Axle)	in. (mm)	25.3 (642) / With optional 9.5-48 wheels = 27.2 (691)				
	Turning radius w/brake	ft. (m)	13.8 (4.2)				
Tire Size	Weight (ROPS/Cab)	lbs. (kg)	7140 (3239) / 7320 (3320)				
	Ag Standard	Front/Rear	13.6-38 R2 Rice and Cane/13.6-38 R2 Rice and Cane				

All standard equipment in base model machines except where noted.

The company reserves the right to change the above specifications without notice.

These Specifications are for descriptive purpose only. Please contact your local Kubota dealer for warranty information.

For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.